

REQUEST FOR ACCESS OF ABANDONED APPLICATION UNDER 37 CFR 1.14(a)

RECEIVED

JUL 23 2001

File Information Unit

In re Application of

Application Number

239978

Filed

5-9-94

Group Art Unit

Examiner

Paper No. 716

Assistant Commissioner for Patents
Washington, DC 20231

I hereby request access under 37 CFR 1.14(a)(3)(iv) to the application file records of the above-identified ABANDONED application, which is: (CHECK ONE)

(A) referred to in United States Patent Number 5748473 column _____

(B) referred to in an application that is open to public inspection as set forth in 37 CFR 1.11, i.e., Application No. _____, filed _____ on page _____ of paper number _____

(C) an application that claims the benefit of the filing date of an application that is open to public inspection, i.e., Application No. _____, filed _____ or

(D) an application in which the applicant has filed an authorization to lay open the complete application to the public.

Please direct any correspondence concerning this request to the following address:

RL H
Signature

7 23 01

Date

Thomas Hazel
Typed or printed name

FOR PTO USE ONLY

Approved by: Tom
(initials)

Unit: E-14

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. This will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

US005748473A

United States Patent [19]

Breed et al.

[11] Patent Number: 5,748,473

[45] Date of Patent: May 5, 1998

[54] AUTOMATIC VEHICLE SEAT ADJUSTER

[75] Inventors: David S. Breed, Boonton Township, N.J.; Wilbur E. DuVall, Kimberling City, Mo.

[73] Assignee: Automotive Technologies International, Inc., Denville, N.J.

[21] Appl. No.: 474,784

[22] Filed: Jun. 7, 1995

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 239,978, May 9, 1994, which is a continuation-in-part of Ser. No. 40,978, Mar. 31, 1993, which is a continuation-in-part of Ser. No. 878,571, May 5, 1992, abandoned.

[51] Int. CL⁶ B60R 21/28

[52] U.S. Cl. 364/424.055; 364/424.059;

280/735; 180/273; 297/410; 307/10.1;

[58] Field of Search 364/424.055, 424.056, 364/424.057, 424.059, 460, 461; 280/734, 735, 736; 297/403, 408, 410; 307/10.1; 340/436, 903; 180/268, 272, 273

[56] References Cited

U.S. PATENT DOCUMENTS

3,275,975	9/1966	King	180/272
4,319,652	5/1983	Kamijo	180/268
4,625,320	11/1986	Ishikawa	382/104
4,545,233	2/1987	Brose et al.	297/410
4,811,226	3/1989	Shiozawa	364/424.059
5,008,946	4/1991	Aado	180/167
5,071,160	12/1991	White et al.	280/735
5,074,583	12/1991	Pujita	280/735
5,118,134	6/1992	Menes	280/735

5,125,686	6/1992	Yano	280/801.2
5,155,685	10/1992	Kishi et al.	364/424.059
5,161,620	11/1992	Vollmer	280/730
5,254,924	10/1993	Ogasawara	364/424.059
5,330,226	7/1994	Gentry et al.	280/735
5,413,378	5/1995	Steffens, Jr. et al.	280/735
5,439,249	8/1995	Steffens, Jr. et al.	280/735
5,454,591	10/1995	Mazar et al.	280/735
5,474,327	12/1995	Schourek	280/735
5,531,472	7/1996	Semchuk et al.	280/735
5,573,269	11/1996	Gentry et al.	280/735

Primary Examiner—Gary Chin

[57] ABSTRACT

An automatic seat adjustment system for a motor vehicle having a passenger compartment with a seat in which an occupant sits. The seat has power mechanisms for moving the seat relative to the passenger compartment from an initial position to an adjusted position, and control mechanisms connected to the power mechanisms for controlling the power mechanisms. Generally, the system includes measurement devices for measuring at least one morphological characteristic of the occupant and generating a first signal representative of the magnitude of that morphological characteristic, a processor including computational means for determining an adjusted seat position based on that measured morphological characteristic and which generates a second signal corresponding to the adjusted seat position, a first input device coupled to the measurement devices and to the processor for inputting the first signal into the processor; and a second input device coupled to the processor and the control mechanisms for inputting the second signal into the control mechanisms. In this manner, the control mechanism is able to affect the operation of the power mechanisms to move the seat to the adjusted position.

20 Claims, 11 Drawing Sheets

